


Product information

Installation Cable Cat. 5e, U/UTP, 4P, 200 MHz, LSZH, Eca, 500 m

R35045
101771911
500 m



Cat. 5e, U/UTP cable. 100 Ohm impedance. Data transmission frequencies of up to 200 MHz.

020.0980 / similar product

Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	ISO/IEC 11801 ed. 2.2: June 2011 IEC 61156-5 2 nd ed. EN 50173-1 EN 50288-3-1 TIA 568-C.2 Fire classification: IEC 60332-1 CPR fire class: EN50575 IEC 61034 IEC 60754-2
Protection class IP	IP 20
PoE	Yes
Cable type	installation cable
Category	Cat. 5e
Shielding	U/UTP
Jacket material	LSZH
Fire rating	Eca
Cable jacket characteristics	Zero-halogen
Cable protection	No protection
Cable overall diameter	Ø 5.1 mm
Wire diameter	AWG 24
Cable design	normal
Number of wires	8
Stranding	4 pairs
Wire type	Wire
Max. test frequency	200 MHz

Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Cable length	500 m
Color Code RAL	7035 Light gray