

Product information

19" 2U Global Patch Panel 48-Port/s, empty

R503806
966733235
1 Pcs.



Holds up to sixteen 2U Global/s connection module holders or 2U Global blind covers. Max. capacity of 48 RJ45/s connection modules.

- 19" 2U Global patch panel/s
- Grounding system
- 19" mounting kit
- Installation instructions

090.3101




Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	UL Listed
Protection class IP	IP 20
PoE	Yes
Shielding connector (A)	shielded
Assembly	empty
Fastening	19 "
Rack mounting version	patch panel
Capacity (ports)	48
Amount of height units	2 U

Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Width	482.6 mm
Height	88.1 mm
Depth	82 mm
Color Code NCS	S 2502-B

Modular patch panel accommodating up to sixteen connection module holders 2U Global/s, installation-friendly thanks to snap-and-go technique, featuring a complete grounding system and 2U Global blind cover. Designed to accommodate the R&M security and the R&M environment system, with its 3-level protection concept: color coding, mechanical coding, locking option. Exchangeable labeling strips, fastening kit, labeling fields, tool-free locking and unlocking system. Automatic ground contacting by spring contacts. Profile aluminum, colorless chromated; side panel plastic (PC), fiberglass-reinforced, halogen-free, color medium gray (NCS 2502-B).

	Description	PU	Product No.
	To be mounted into 19" 2U Global patch panels, shielded. Holding capacity: 3 connection modules RJ45/s.	1 Pcs.	R503813
	For use with 19" 2U Global patch panels, shielded and unshielded.	1 Pcs.	R316871
	For vertical cable management with the Global 2U patch panel. Fast installation – slides under Global 2U panel mounting screws. Flexible – mounts on left or right outside of panel. Saves space through higher port densities.	1 Pcs.	R505851