Product information

Patch Cord Cat. 6, U/UTP, 4P, LSZH, gray, RJ45/u-RJ45/u, 0.5 m

R302309 101347095 10 Pcs.



090.6826 / similar product

Cable identification: U/UTP Outer jacket: LSZH

Conductor diameter copper strand: AWG 26/7

Screened in pairs: no Overall screen: no Outer diameter: max. 6.0 mm

Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	Compliant with Cat. 6, Class E (250 MHz) requirements: ISO/IEC 11801 ed. 2.2 Compliant with Cat. 6 component standard IEC 60603-7-4 Compliant with Cat. 6 component standard IEC 60603-7-5 Fulfilled the standard IEC 61935-2:2010
Protection class IP	IP 20
PoE	Yes
Connector class	connector
Shielding connector (A)	unshielded
Connector type (A)	RJ45
Category connector (A)	Cat. 6
Shielding connector (B)	unshielded
Connector type (B)	RJ45
Category connector (B)	Cat. 6
Cable type	patch cord
Category	Cat. 6
Shielding	U/UTP
Jacket material	LSZH
Cable jacket characteristics	Cable, metal-free Zero-halogen
Cable overall diameter	6.0 mm
Wire diameter	AWG 26/7
Number of wires	8
Stranding	4 x 2 pairs
Wire type	stranded wire

Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Cable length	0.5 m
Color Code RAL	7035 Light gray

Flexible cable, U/UTP, $4 \times 2 \times AWG$ 26/7, LSZH, color gray (RAL 7035). Low-smoke in acc. with IEC 61034 and halogen-free in acc. with IEC 60754-1. Halogen-free and heavy-metal free in acc. with EU directives RoHS 2. Mounted on both sides with

RJ45 connector compliant with Cat. 6 component standard. Key standard: IEC 60603-7 RJ45 category 6; IEC 60603-7-1 to 5. Strain-relief function in acc. with TIA 568-C.

Complies with requirements of Cat. 6 for the establishing of transmission links of class E in acc. with ISO/IEC 11801 ed. 2.2, June 2011 and EN 50173-1, May 2011 (DIN EN 50173-1). Optional:

Visual coding, mechanical coding and lock protection.

Description	PU	Product No.
Color coding for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R302342
Color coding for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R302343
Color coding for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R302344
Color coding for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R302345
Color coding for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R302347

Description	PU	Product No.
Color coding for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R302348
Color coding for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R302349
Color coding for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R302420
Easy Latch for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R317100
Easy Latch for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R317094
Easy Latch for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R317095
Easy Latch for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R317096

Description	PU	Product No.
Easy Latch for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R317097
Easy Latch for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R317098
Easy Latch for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R317099
Easy Latch for RJ45 patch cords and consolidation point patch cords.	20 Pcs.	R317093
Elastic, transparent rubber sleeve suitable for all RJ45 patch cords. Together the Splash sleeve and the Splash cap offer protection class IP54.	10 Pcs.	R306064
Color code: blue, red, green, anthracite. Suitable for RJ45 patch cords.	20 Pcs.	R25432
Color code: yellow, brown, violet, white. Suitable for RJ45 patch cords.	20 Pcs.	R25677

Description	PU	Product No.
Locking element for RJ45 patch cords (R&M standard patch cords), protecting connections from being unplugged by mistakes.	20 Pcs.	R304807
Lockable plug-out protection for RJ45 connecting cables (R&M standard patch cables). Color coding with color clip.	20 Pcs.	R313814
For the tool-free retrofitting of 10 RJ45 patch cords with R&MinteliPhy functions. Compatible with R&M patch cords.	1 Pcs.	R809348