


Product information

Central Loose Tube Cable I/A-DQ(ZN=B)H, OM2, Eca, 24-fibers

R304092
2000 m



This cable construction features a central gel-filled loose tube with a diameter of 2.8 mm for 2 - 16 fibers or 3.5 mm for 18 - 24 fibers. The reinforced glass yarns enhance strength and tensile force and is making it to your ideal partner for secondary cabling applications (backbone) in generic cabling systems. Sheath: LSZH, green. Fiber: multimode (MM) G50/125.

030.1402.1 / similar product

Technical Data

| DESCRIPTION [UNIT] | VALUE/VALUE RANGE |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard | IEC 60794-1-2 E11 IEC 60794-1-2 E3 IEC 60794-1-2 F1 IEC 60332-3C IEC 61034 IEC 60754-2 ISO/IEC 11801:2002 IEC 60794-1-2 E1 |
| Cable type | loose tube |
| Jacket material | LSZH |
| Fire rating | Eca |
| Cable jacket characteristics | Cable, water-tight |
| Cable protection | Rodent protection |
| Cable overall diameter | 7.0 mm |
| Cable design | I/A-DQ(ZN=B)H |
| Fiber type | multimode (MM) |
| Fiber class | OM2 |
| Number of fibers | 24 |
| Conductor type | loose tube, gel-filled |
| Fiber diameter | G50 / 125 µm |

Mechanical Data

| DESCRIPTION [UNIT] | VALUE/VALUE RANGE |
|--------------------|-------------------|
| Cable length | 2000 m |
| Color | green |