## **Product information**

Adapter SC-Duplex PC, beige, ceramic MM, M, screwable

R317064 12 Pcs.



- SC-Duplex adapter
- 2 Philips head screws M2 x 8, blue galvanized
- 2 mounted hexagonal nuts M2, blue galvanized

090.2443 / similar product

## **Technical Data**

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	according to IEC 61754-4 UL Listed
Protection class IP	IP 20
Connector class	adapter
Number of connectors (A)	1
Connector type (A)	SC-Duplex
Polishing plug (A)	PC
Attenuation grade IL (A)	М
Connector color (A)	beige
Sleeve material	ceramic
Adapter fastening method	end cap
Fiber type	multimode (MM)

SC-Duplex adapter multimode in acc. with IEC 61754-4. Body plus flange and two hexagonal nuts M2 plus integral quick-mounting clip. Zirconia (ceramic) alignment sleeve, beige plastic housing (multimode) / UL 94 V-0, plastic dust cover. Adapter qualified in acc. with IEC 61753-1 for category U (uncontrolled environment). Optical specifications:

• Delta insertion loss:  $\leq$  0.2 dB, testing method acc. to IEC 61300-3-4

Mechanical specifications:

• Mating cycles: min. 500

• Pull-out force: min. 70 N (per connector)

