


Product information

Connector SC PC, MM, beige, 127.0 (+3/-0) µm

R304375
100 Pcs.



090.6034

Locking type push-pull. Injection-molded PBT housing, UL 94 V-0 (flammability index).

- Inner and outer connector housings
- Ferrule holder incl. ferrule

Technical Data





DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	UL Listed
Protection class IP	IP 20
Connector class	connector
Protection class IP (A)	IP 20
Number of connectors (A)	1
Connector type (A)	SC
Polishing plug (A)	PC
Attenuation grade IL (A)	Bm
Connector color (A)	beige
Fiber type	multimode (MM)

Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Diameter	127 µm

	Description	PU	Product No.
	Colored connector boot, short version, 13.5 mm length. For tubes from Ø 0.6 - 1.2 mm. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R810595

	Description	PU	Product No.
	Colored connector boot. For tubes from Ø 0.6 - 1.2 mm. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R504383
	Crimp sleeve and colored connector boot. For cables from Ø 1.4 - 1.7 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R812803
	Crimp sleeve and colored connector boot. For cables from Ø 1.4 - 1.7 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R812804
	Crimp sleeve and colored connector boot. For cables from Ø 1.8 - 2.2 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R812807
	Crimp sleeve and colored connector boot. For cables from Ø 1.8 - 2.2 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R812808
	Crimp sleeve and colored connector boot. For cables from Ø 2.3 - 2.6 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R813158
	Crimp sleeve and colored connector boot. For cables from Ø 2.3 - 2.6 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R813159

	Description	PU	Product No.
	Crimp sleeve and colored connector boot. For cables from Ø 2.7 - 3.0 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R813162
	Crimp sleeve and colored connector boot. For cables from Ø 2.7 - 3.0 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R813163
	With the subsequent mountable 90° boot existing or new networks can be updated. The 90° boot guarantees an optimised fiber guidance (R>30 mm), even by load caused by the cable. An uncontrolled fiber bending and resulting attenuation or even broken fiber can be avoided in no time.	12 Pcs.	R505756
	This clip makes SC-Duplex applications possible. Color: black.	1 Pcs.	R306718