## **Product information**

Connector Crimp and Cleave PCF, SC-RJ PC, MM, beige, 232.0 (+2/-0) µm

R810634 25 Pcs.



Field-terminable SC-RJ / PC connector, Grade Em. Color beige.

- Connector housings and plastic dust covers
- Ferrule holder incl. ferrule

090.7015

## **Technical Data**

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	SC-RJ (duplex) connector acc. to IEC 61754-24
Protection class IP	IP 20
Connector class	connector
Protection class IP (A)	IP 20
Connector type (A)	SC-RJ
Polishing plug (A)	NPC
Attenuation grade IL (A)	Em
Fiber type	multimode (MM)

Field-terminable connector, SC-RJ PC, grade Em, in compliance with IEC 61754-24 (SC duplex). Connector housing made of PBT / UL 94 V-0, beige, (multimode PC) and plastic dust covers. Glueless assembling, fiber fixation by clamping (crimp) and fiber end cleaving.

Description	PU	Product No.
Crimp sleeve and colored connector boot. For cables from Ø 2.7 - 3.0 mm. Material sleve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R813162
	2000 m	R313540

Description	PU	Product No.
	2000 m	R313539
Color coding for SC-RJ patch cord, Fiber Guard, coding frame and Patch Guard.	12 Pcs.	R310142
Color coding for SC-RJ patch cord, Fiber Guard, coding frame and Patch Guard.	12 Pcs.	R310147
Assembling tool for connector crimp and cleave PCF.	1 Pcs.	R810636