

Product information

19" 3U Global Patch Panel 60-Port/u, empty

R35409
966730385
1 Pcs.



Holds up to fifteen Global/u connection module holders, Global blind covers or six Global adapter units. Max. capacity of 60 RJ45/u connection modules.

- 19" 3U Global patch panel/u incl. cable tie shelf
- 19" mounting kit
- Installation instructions

010.2055


Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	UL Listed
Protection class IP	IP 20
PoE	Yes
Shielding connector (A)	unshielded
Assembly	empty
Fastening	19 "
Rack mounting version	patch panel
Capacity (ports)	60
Amount of height units	3 U

Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Width	482.6 mm
Height	132.5 mm
Depth	221 mm

Modular patch panel accommodating up to fifteen connection module holders Global/u, installation-friendly thanks to snap-and-go technique, Global blind cover or FiberModul 5.6HP. Designed to accommodate the R&M security and the R&M environment system, with its 3-level protection concept: color coding, mechanical coding, locking option. Exchangeable labeling strips, integral cable tie shelf, fastening kit, labeling fields, tool-free locking and unlocking system. Profile aluminum, colorless chromated; cable tie shelf sheet steel (DC01A) 1.5 mm, color blue passivated; side panel plastic (PA), fiberglass-reinforced, halogen-free, color medium gray (NCS 2502-B).

	Description	PU	Product No.
	<p>To be mounted into 19" 3U Global patch panels, unshielded. Holding capacity: 4 connection modules RJ45/u or 4 SC-RJ or E-2000™-Compact adapters.</p>	1 Pcs.	R35403
	<p>To be mounted into 19" 3U Global patch panels. Max. equipped with 5 voice adapters (150 ports). Holding capacity for 3 connection modules 10xRJ45.</p>	1 Pcs.	R310400
	<p>For use with 19" 3U Global patch panels, shielded and unshielded.</p>	1 Pcs.	R35401
	<p>Recommended for multipair telephone cables. Mounted onto the cable tie shelf of the 3U Global patch panel, the cable duct ensures optimum cable management.</p>	1 Pcs.	R310401
	<p>For vertical cable management with the Global 3U patch panel. Fast installation – slides under Global 3U panel mounting screws. Flexible – mounts on left or right and on inside or outside of panel. Saves space through higher port densities. Width: 1.5 GU</p>	1 Pcs.	R316247