


Product information

Adapter LC-Duplex PC, blue, ceramic SM, C, flangeless

R820419
12 Pcs.



LC-Duplex adapter flangeless with semi-transparent dust caps. Quick mounting clip integrated.

090.7330

Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	UL Listed according to IEC 61754-20
Connector class	adapter
Protection class IP (A)	IP 20
Number of connectors (A)	1
Connector type (A)	LC-Duplex
Polishing plug (A)	PC
Attenuation grade IL (A)	C
Connector color (A)	blue
Sleeve material	ceramic
Adapter fastening method	end cap snap-in
Fiber type	singlemode (SM)

Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Width	55 mm
Height	15.5 mm
Depth	9.35 mm

LC-Duplex singlemode adapter in acc. with IEC 61754-20. Flangeless body and integrated quick-mounting clip, color metallic, material X10CrNi18-8. Housing blue (singlemode PC), material PBT / UL 94 V-0, zirconia (ceramic) alignment sleeve, integral self-closing metal laser protection flaps, semi-transparent plastic dust covers, allowing optical testing with test lasers without removing the covers. The adapter qualified in acc. with IEC 61753-1 for category U (uncontrolled environment).

Optical specifications:


- Delta insertion loss: ≤ 0.2 dB, testing method acc. to IEC 61300-3-4

Mechanical specifications:

- Mating cycles: min. 500
- Pull-out force: min. 70

Optional:

Visual coding, mechanical coding and lock protection.

	Description	PU	Product No.
	45° Clip for LSH/LCd/SC adapter (flange less!)	10 Pcs.	R815789