


## Product information

### Adapter LC-Duplex PC, beige, ceramic MM, M, screwable

R820417  
12 Pcs.



Adapter LC-Duplex with semi-transparent dust caps. Quick mounting clip and M2 thread integrated.

- Adapter LC-Duplex
- 2 Philips head screws M2 x 8, blue galvanized

090.7335

### Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	UL Listed according to IEC 61754-20
Connector class	adapter
Protection class IP (A)	IP 20
Number of connectors (A)	1
Connector type (A)	LC-Duplex
Polishing plug (A)	PC
Attenuation grade IL (A)	M
Connector color (A)	beige
Sleeve material	ceramic
Adapter fastening method	end cap
Fiber type	multimode (MM)

### Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Width	55 mm
Height	22 mm
Depth	9.35 mm

LC-Duplex multimode adapter in acc. with IEC 61754-20. Adapter body plus flange and integral quick-mounting clip and M2 thread, color metallic, material X10CrNi18-8. Housing beige (multimode PC), material PBT / UL 94 V-0, zirconia (ceramic) alignment sleeve, integral self-closing metal laser protection flaps, semi-transparent plastic dust covers, allowing optical testing with test lasers without removing the covers. The adapter qualified in acc. with IEC 61753-1 for category U (uncontrolled environment).

Optical specifications:

- Delta insertion loss:  $\leq 0.2$  dB, testing method acc. to IEC 61300-3-4

Mechanical specifications:

- Mating cycles: min. 500

- Pull-out force: min. 70 N

Optional:

Visual coding, mechanical coding and lock protection.