

Product information

Connector SC-RJ PC, MM, black, 232.0 (+2/-0) µm

R802164
50 Pcs.



Locking type push-pull. Injection-molded PBT housing, UL 94 V-0 (flammability index).

- Inner and outer connector housings
- 2 Ferrule holders incl. ferrules

090.6035

Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	Duplex connectors in acc. with IEC 61754-24
Protection class IP	IP 20
Connector class	connector
Protection class IP (A)	IP 20
Number of connectors (A)	1
Connector type (A)	SC-RJ
Polishing plug (A)	PC
Attenuation grade IL (A)	Bm
Connector color (A)	black
Fiber type	multimode (MM)

	Description	PU	Product No.
	Colored connector boot, short version, 13.5 mm length. For tubes from Ø 0.6 - 1.2 mm. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R810595
	Colored connector boot. For tubes from Ø 0.6 - 1.2 mm. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R504383

	Description	PU	Product No.
	Crimp sleeve and colored connector boot. For cables from Ø 1.4 - 1.7 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R812803
	Crimp sleeve and colored connector boot. For cables from Ø 1.4 - 1.7 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R812804
	Crimp sleeve and colored connector boot. For cables from Ø 1.8 - 2.2 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R812807
	Crimp sleeve and colored connector boot. For cables from Ø 1.8 - 2.2 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R812808
	Crimp sleeve and colored connector boot. For cables from Ø 2.3 - 2.6 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R813158
	Crimp sleeve and colored connector boot. For cables from Ø 2.3 - 2.6 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R813159
	Crimp sleeve and colored connector boot. For cables from Ø 2.7 - 3.0 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.	100 Pcs.	R813162

	Description	PU	Product No.
	<p>Crimp sleeve and colored connector boot. For cables from Ø 2.7 - 3.0 mm. Material sleeve: aluminum. Material boot: TPE, self extinguishing, free of halogen.</p>	100 Pcs.	R813163
	<p>With the subsequent mountable 90° boot existing or new networks can be updated. The 90° boot guarantees an optimised fiber guidance ($R > 30$ mm), even by load caused by the cable. An uncontrolled fiber bending and resulting attenuation or even broken fiber can be avoided in no time.</p>	12 Pcs.	R505756
	<p>Color coding for SC-RJ patch cord, Fiber Guard, coding frame and Patch Guard.</p>	12 Pcs.	R310142